TMR / TGR | Rigid Sun Tunnel® Pricing

- Package includes dome, shingle/shake roof flashing, tunnel, two adjustable elbows, ceiling ring and diffuser.
- Flashings for tile roofs are optional.
- For flat roof application call VELUX.

- Light kit allows you to use the skylight as an extra light source even at night.
- Pitch adapter creates straight tunnel run maximizing light output.

15° - 60°
3:12 - 20:12

TMR | Rigid pitched flashing units

Size code		010	014
Rough opening		10" Diameter	14" Diameter
Rigid tubing length with kit (Subtract approximately 6" for flashing)		4'	4'
Maximum recommended installation length		14'	18'
Dome / flashing	Model number	$	$
Acrylic dome / Shingle or shake roof	TMR	289	409
Accessories	Model number	$	$
Universal electric light kit	ZTL 114	45	45
2 ft rigid tunnel extension	ZTR 2'	36	50
4 ft rigid tunnel extension	ZTR 4'	59	98
6 ft rigid tunnel extension	ZTR 6'	82	146
Tile kit for pitched flashing units	ZTM 000050	215	245
Turret extender	ZTA	40	45
NEW SIZE Roofing underlayment (12"x21')	ZOZ 211	29	29

TGR | Rigid low profile flashing units

Size code		010	014
Rough opening		10" Diameter	14" Diameter
Rigid tubing length with kit (Subtract approximately 6" for flashing)		4'	4'
Maximum recommended installation length		14'	18'
Dome / flashing	Model number	$	$
Acrylic dome / Shingle or shake roof	TGR	279	399
Accessories	Model number	$	$
Universal electric light kit	ZTL 114	45	45
2 ft rigid tunnel extension	ZTR 2'	36	50
4 ft rigid tunnel extension	ZTR 4'	59	98
6 ft rigid tunnel extension	ZTR 6'	82	146
Tile kit for pitched flashing units	ZTM 000050	215	245
Turret extender	ZTA	40	45
NEW SIZE Roofing underlayment (12"x21')	ZOZ 211	29	29

TMF / TGF | Flexible Sun Tunnel® Pricing

- Package includes dome, shingle/shake roof flashing, flexible tunnel, two adjustable elbows, ceiling ring and diffuser.
- Flashings for tile roofs are optional.
- For flat roof application call VELUX.

- Light kit allows you to use the skylight as an extra light source even at night.
- Flexible tunnel bends around attic obstructions.

15° - 60°
3:12 - 20:12

TMF | Flexible pitched flashing units

Size code		014
Rough opening		14" Diameter
Flexible tubing length with kit		8'
Maximum recommended installation length		8'
Dome / flashing	Model number	$
Acrylic dome / Shingle or shake roof	TMF	409
Accessories	Model number	$
Universal electric light kit	ZTL 114	45
10 ft flexible tunnel replacement	ZTF 10'	35
Tile kit for pitched flashing units	ZTM 000050	245
Turret extender	ZTA	45
NEW SIZE Roofing underlayment (12"x21')	ZOZ 211	29

TGF | Flexible low profile flashing units

Size code		014	021
Rough opening		14" Diameter	21" Diameter
Flexible tubing length with kit		8'	6'
Maximum recommended installation length		8'	12'
Dome / flashing	Model number	$	$
Acrylic dome / Shingle or shake roof	TGF	399	529
Accessories	Model number	$	$
Universal electric light kit	ZTL 114	45	N/A
Universal electric light kit	ZTL 122	N/A	50
10 ft flexible tunnel replacement	ZTF 10'	35	N/A
12 ft flexible tunnel replacement	ZTF 12'	N/A	60
Tile kit with skirt	ZTG 0000	N/A	99
Tile kit with skirt and turret	ZTG S00001	N/A	119
Turret extender	ZTA	45	54
NEW SIZE Roofing underlayment (12"x21')	ZOZ 211	29	29

Codes and Approvals

- NFRC Certified
- Hallmark Certified
- Energy Star® Approved
- Tested to: AAMA/WDMA/CSA 101/ I.S.2/A440.05
- Tested to: AAMA/WDMA 101/I.S.2/ NAFS-02

Sun Tunnel Skylights®

How to Choose Your Sun Tunnel Skylight:

1. Consider Roof Orientation
- Pitched model (N,S,E,W exposure).
- Low profile model (S. exposure only).

2. Choose Tunnel Type
- Rigid - For straight runs and moderate bends. Maximum light output.
- Flexible - Easily bends around attic obstructions.

3. Choose Sun Tunnel Size and Quantity
- 10", 14" or 21".
- Consider truss/rafter spacing.
- Consider room size and light requirements.

Pitched Flashing N, S, E, W exposures	010	014	021
	Light Coverage	Light Coverage	Light Coverage
Rigid Tunnel	Up to 200 sq. ft. Model TMR 10	200 to 325 sq. ft. Model TMR 14	N/A
Flexible Tunnel	N/A	Up to 200 sq. ft. Model TMF 14	See TGF 21" option
Low Profile Flashing South exposures only			
Rigid Tunnel	Up to 200 sq. ft. Model TGR 10	200 to 325 sq. ft. Model TGR 14	N/A
Flexible Tunnel	N/A	Up to 150 sq. ft. Model TGF 14	150 to 325 sq. ft. Model TGF 21

Chart is based on month of June and is intended as a guideline only.

Rigid Sun Tunnel Skylights
Maximum light output

Flexible Sun Tunnel Skylights
Easily installed